

Pedestal Server Chassis Overview

Rackmount Chassis

Pedestal Server

Storage Kits

Card Kit

Accessories

| Volume (DP)                                                                                  |                                                                                     |
|----------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| SR105                                                                                        | SR107/SR108                                                                         |
|             |  |
| Extended ATX (12" x 13"),<br>CEB (12" x 10.5"), ATX (12" x 9.6")                             | Extended ATX (12" x 13"),<br>CEB (12" x 10.5"), ATX (12" x 9.6")                    |
| 533 mm x 198 mm x 425 mm<br>20.9" x 7.8" x 16.7"                                             | 620 mm x 220 mm x 425 mm<br>22.4" x 8.7" x 16.7"                                    |
| 5.25" x 3<br>3.5" x 1 (5.25" to 3.5" bracket)(Optional)                                      | 5.25" x 3<br>3.5" x 1                                                               |
| 4 (Optional HDD cage, P73)                                                                   | 8 (Optional HDD cage, P73)                                                          |
| 3.5" x 4 (Optional HDD cage, P73)                                                            | 3.5" x 8 (Optional HDD cage, P73)                                                   |
| PS/2,<br>1 + 1 Mini-Redundant                                                                | PS/2,<br>N+1 Redundant                                                              |
| 600 W or above                                                                               | 600 W or above                                                                      |
| 1 x Power LED/<br>1 x HDD Activity LED/Fault LED,<br>2 x LAN Activity LEDs                   | 1 x Power LED/<br>1 x HDD Activity LED/Fault LED,<br>2 x LAN Activity LEDs          |
| Power ON/OFF, Alarm Mute,<br>System Reset, 2 x USB 2.0 Ports                                 | Power ON/OFF, Alarm Mute,<br>System Reset, 2 x USB 2.0 Ports                        |
| Intrusion Switch, Key Lock,<br>Kensington Lock Supported                                     | Intrusion Switch, Key Lock,<br>Kensington Lock Supported                            |
| Front :<br>1 x 92 mm (Optional),<br>1 x 80 mm (On Hot-swap cage)<br>Rear :<br>1 x 120 mm PWM | Middle :<br>2 x 120 mm, 2 x 120 mm Hot-swap (SR108)<br>Rear :<br>1 x 120 mm PWM     |
| 7 (5 x full length + 2 x half length)                                                        | 7 (6 x full length, 1 x half length)                                                |
| ABS-HB                                                                                       | ABS-HB                                                                              |
| SECC/0.8 mm                                                                                  | SECC/1.0 mm                                                                         |
| 9 Kg                                                                                         | 18 Kg                                                                               |
| 11 Kg                                                                                        | 22.5 Kg                                                                             |
| 6Gb/s SATA<br>6Gb/s Mini-SAS                                                                 | 6Gb/s SATA<br>6Gb/s Mini-SAS                                                        |
| Optional                                                                                     | Optional                                                                            |
| 3.05 (SR10562,67,69)<br>3.15 (SR10565,66,68)                                                 | 5.53                                                                                |
| 20' : 297/311<br>40' : 621/636 (SR10565,66,68/10567,69)<br>40'H : 736/752                    | 20' : 168<br>40' : 344<br>40'H : 404                                                |
| 20' : 288<br>40' : 528<br>40'H : 572                                                         | 20' : 140<br>40' : 280<br>40'H : 336                                                |
| 20' : 320/348<br>40' : 720<br>40'H : 900/X                                                   | 20' : 224<br>40' : 480                                                              |

| Performance (DP)                                                                    |  | Value Added (UP)                                                                             |  |
|-------------------------------------------------------------------------------------|--|----------------------------------------------------------------------------------------------|--|
| SR112                                                                               |  | SR209                                                                                        |  |
|  |  |           |  |
| Extended ATX (12" x 13")<br>CEB (12" x 10.5"), ATX (12" x 9.6")                     |  | ATX (12" x 9.6")                                                                             |  |
| 620 mm x 220 mm x 425 mm<br>24.4" x 8.7" x 16.7"                                    |  | 465 mm x 198 mm x 425 mm<br>18.3" x 7.8" x 16.7"                                             |  |
| 5.25" x 2                                                                           |  | 5.25" x 3<br>3.5" x 1 (5.25" to 3.5" bracket)(Optional)                                      |  |
| 3.5" : 2                                                                            |  | 4 (Optional HDD cage, P73)                                                                   |  |
| 3.5" x 8 (Fixed or H/S) or<br>2.5" x 16 (H/S)                                       |  | 3.5" x 4 (Optional HDD cage, P73)                                                            |  |
| PS/2,<br>N+1 Redundant                                                              |  | PS/2                                                                                         |  |
| 600 W or above                                                                      |  | 600 W or above                                                                               |  |
| 1 x Power LED/<br>1 x HDD Activity LED/Fault LED,<br>2 x LAN Activity LEDs          |  | 1 x Power LED/<br>1 x HDD Activity LED/Fault LED,<br>2 x LAN Activity LEDs                   |  |
| Power ON/OFF, Alarm Mute,<br>System Reset, 2 x USB 2.0 Ports                        |  | Power ON/OFF, Alarm Mute,<br>System Reset, 2 x USB 2.0 Ports                                 |  |
| Intrusion Switch, Key Lock,<br>Kensington Lock Supported                            |  | Intrusion Switch, Key Lock,<br>Kensington Lock Supported                                     |  |
| Middle :<br>3 x 92 mm PWM<br>Rear :<br>1 x 120 mm PWM                               |  | Front :<br>1 x 92 mm (Optional),<br>1 x 80 mm (On Hot-swap cage)<br>Rear :<br>1 x 120 mm PWM |  |
| 7 (6 x full length, 1 x half length)                                                |  | 7 (5 x full length, 2 x half length)                                                         |  |
| ABS-HB                                                                              |  | ABS-HB                                                                                       |  |
| SECC/1.0 mm                                                                         |  | SECC/0.8 mm                                                                                  |  |
| 15.5 Kg                                                                             |  | 7.8 Kg                                                                                       |  |
| 20 Kg                                                                               |  | 9.8 Kg                                                                                       |  |
| 6Gb/s SATA<br>6Gb/s Mini-SAS                                                        |  | 6Gb/s SATA<br>6Gb/s Mini-SAS                                                                 |  |
| Optional                                                                            |  | Optional                                                                                     |  |
| 5.53                                                                                |  | 2.94<br>2.69                                                                                 |  |
| 20' : 168<br>40' : 344<br>40'H : 404                                                |  | 20' : 350<br>40' : 734<br>40'H : 820                                                         |  |
| 20' : 140<br>40' : 280<br>40'H : 336                                                |  | 20' : 260<br>40' : 520<br>40'H : 640                                                         |  |
| 20' : 224<br>40' : 480                                                              |  | 20' : 400<br>40' : 880<br>40'H : 1100                                                        |  |

Rackmount Chassis

Pedestal Server

Storage Kits

Card Kit

Accessories