

PC Chassis Series

Desktop/Tower Chassis

PC710/711

PC713

Model



Spec.

M/B Form Factor		Micro ATX	Micro ATX
Dimension (D×W×H)*		395 x 95 x 325 (mm), 15.6" x 3.7" x 12.8"	328 x 112 x 390 (mm), 12.7" x 4.4" x 15.4"
Drive Bay	Exposed	5.25" x 1, 3.5" x 1	5.25" x 1
	Internal	3.5" x 1	3.5" x 1, 2.5" x 1
	Card Reader	N/A	N/A
PSU Form Factor		TFX	TFX
Indicator		Power Status x 1, HDD Activity x1	Power Status x 1, HDD Activity x1
Front Control		Power On/Off, USB 2.0 x 2, Audio x 2, Reset x 1, IEEE 1394 x 0 or 1	Power On/Off, USB 2.0 x 2, USB 3.0 x 2, Audio x 2
System Security		Kensington Slot, Intrusion Switch	Kensington Slot, Padlock Loop, Intrusion Switch
Cooling Fan	Front	N/A	80 mm x 1 (Option)
	Rear	Side : 80 mm x 1	60mm x 1
Slot Opening		Low Profile x 4	Low Profile x 4
Sheet Metal Material		SECC	SGCC
Metal Thickness		0.8 mm	0.6 mm
Net Weight		5.8 kg	3.6 kg
Gross Weight		8.0 kg	4.5 kg
Cubic Feet		1.44	1.59
Container Loading	Single Packing	20' : 720 40' : 1,500	20' : 606 40' : 1,291 40'HQ : 1,435
	Bulk Packing + Pallet	20' : 1,080 40' : 2,160	20' : 960 40' : 1,920 40'HQ : 2,400

Desktop/Tower Chassis

PC719

PC722

Mid - Tower Chassis

PC617



M/B Form Factor		Micro ATX	Micro ATX	ATX
Dimension (D×W×H)*		300 x 90 x 326 (mm), 11.8" x 3.5" x 12.8"	300 x 90 x 326 (mm), 11.8" x 3.5" x 12.8"	465 x 198 x 425 (mm), 18.3" x 7.8" x 16.7"
Drive Bay		Slim ODD x 1, Slim FDD x 1	Slim ODDx 1, Slim FDDx 1	5.25" x 4, 3.5" x 1 or 2 (bezel dependant)
Card Reader		3.5" x 1	2 x 2.5" or 3 x 2.5" (Occupy slim FDD bay)	3.5" x 2 or 1
PSU Form Factor		SD/Mini-SD/MMC/MS x 1 (Option)	N/A	N/A
Indicator		TFX	TFX	PS/2
Front Control		Power Status x 1	Power Status x 1, HDD Activity x1	Power Status x 1, HDD Activity x1
System Security		Power On/Off, USB 2.0 x 2, Audio x 2, System Reset x 1, IEEE 1394 x 0 or 1, CF/SD/MMC/MS-PRO/SM	Power On/Off, USB2.0 x 2, USB3.0 x 2, Audio x 2	Power On/Off, USB 2.0 x 2, Audio x 2, Reset x 1, IEEE 1394 x 0 or 1
System Security		Kensington Slot, Intrusion Switch	Kensington Slot, Padlock Loop, Intrusion Switch	Kensington Slot, Padlock Loop, Intrusion Switch
Cooling Fan	Front	N/A	N/A	92 mm x 1, or 120 mm x 1
	Rear	Bottom: 60 mm x 1	Side: 1 x 60 mm (Option)	80 mm x 1, 92 mm x 1, or 120 mm x 1
Slot Opening		Full Height x 4	Full Height x 4	Full Height x 7
Sheet Metal Material		SECC	SGCC	SECC
Metal Thickness		0.6 mm	0.6 mm	0.7 mm
Net Weight		2.9 kg	3.0 kg	8.2 kg
Gross Weight		3.8 kg	3.6 kg	9.4 kg
Cubic Feet		0.88	0.88	2.69
Container Loading	Single Packing	20' : 1,200 40' : 2,400 40'HQ : 2,670	20' : 1,200 40' : 2,400 40'HQ : 2,670	20' : 364 40' : 748 40'HQ : 842
	Bulk Packing + Pallet	20' : 1,260 40' : 2,520 40'HQ : 3,024	20' : 1,260 40' : 2,520 40'HQ : 3,024	20' : 400 40' : 880 40'HQ : 1,100

*Bezel not included