



PC719

Micro ATX Slim Desktop/Tower Chassis

Features & Benefits

- Support Intel Sandy-Bridge platform thermal requirement
- Support 60mm side(bottom) fan installation and air duct
- Removable drive cage for easy HDD installation
- Pre-punched motherboard stand-off for quick installation
- Adjustable air duct for different CPU locations
- Built-in washable air filter
- Security provision:
Padlock loop, Kensington slot and intrusion switch

Specification

Model Name	• PC719
M/B Form Factor	• Micro ATX
Dimension (D×W×H)	• 300 x 90 x 326 (mm), 11.8" x 3.5" x 12.8"
Drive Bay	• Exposed : Slim ODD x 1, Slim FDD x 1 • Internal : 3.5" x 1 • Card Reader : SD/Mini-SD/MMC/MS x 1 (Option)
PSU Form Factor	• TFX
Indicator	• Power Status x 1
Front Control	• Power On/Off, USB 2.0 x 2, Audio x 2, HDD Activity x 1, CF/SD/MMC/MS-PRO/SM
System Security	• Kensington Slot, Padlock Loop, Intrusion Switch
Cooling Fan	• Bottom : 60 mm x 1
Slot Opening	• Low Profile x 4
Sheet Metal Material	• SECC
Metal Thickness	• 0.6 mm



Front Control : System Reset (Bezel Dependant), IEEE 1394 (Option)



Optional card reader Removable drive cage Slim ODD, Slim FDD, internal 3.5" bays Side (bottom) 1 x bottom 60 mm fan Optional TFX PSU

